Selftest

Version:	1.4ABN(UTP)Q
Command mode:	EPSON(ESC/POS)-S
Interface:	USB & Serial 19200,None,8,1 & Ethernet(10Base/100Base)
Protocols:	TCP/IP (C1) (9100 4000)
Mac address:	00-47-50-4C-80-D3(Hex)
IP address:	192.168.123.100
Netmask:	255.255.255.0
Gate Way:	192.168.123.1
DHCP:	Disabled
Cutter:	Yes
Beeper:	Yes
Chinese character mode:	No
Cutter with drawer:	No
Character per line:	48-fontA/64-fontB
Print Density:	Light
Default code page:	page 2
Black mark mode:	No
Paper end copy mode:	No
Near PE sensor enable:	No
Vertical motion units:	0.5
USB number is fixed:	Yes
ASCII Font TYPE:	FontA
Print Speed:	250mm/s(Max)
Modify date:	2016/12/06

Resident Character:
Alphanumeric

Code Page:

0:PC437(Std.Europe)	1:(Katakana)
2:PC850(Multilingual)	3:PC860(Portuguese)
4:PC863(Canadian)	5:PC865(Nordic)
6:(West Europe)	7:(Greek)
8:(Hebrew)	9:(East Europe)
10:(Iran)	16:(WPC1252)
17:PC866(Cyrillic#2)	18:PC852(Latin2)
19:(PC858)	20:(IranII)
21:(Latvian)	22:(Arabic)
23:(PT151,1251)	24:(PC747)
25:(WPC1257)	27:(Vietnam)
28:(PC864)	29:(PC1001)
30:(Uigur)	31:(Hebrew)
32:WPC1255(Israel)	33:PC720(Arabic)
34:WPC1256(Arabic)	35:WPC1257(N)
36:Armenian	37:PC857(Turkish)
38:WPC1254(Turkish)	255:(Thai)
50:PC437(Std.Europe)	51:(Katakana)
52:PC437(Std.Europe)	53:PC858(Multilingual)
54:PC852(Latin-2)	55:PC860(Portuguese)
56:PC861(Icelandic)	57:PC863(Canadian)
58:PC865(Nordic)	59:PC866(Russian)
60:PC855(Bulgarian)	61:PC857(Turkey)
62:PC862(Hebrew)	63:PC864(Arabic)
64:PC737(Greek)	65:PC851(Greek)
66:PC869(Greek)	67:PC928(Greek)
68:PC772(Lithuanian)	69:PC774(Lithuanian)
70:PC874(Thai)	71:WPC1252(Latin-1)
72:WPC1250(Latin-2)	73:WPC1251(Cyrillic)
74:PC3840(IBM-Russian)	75:PC3841(Gost)
76:PC3843(Polish)	77:PC3844(CS2)
78:PC3845(Hungarian)	79:PC3846(Turkish)
80:PC3847(Brazil-ABNT)	81:PC3848(Brazil-ABICOMP)
82:PC1001(Arabic)	83:PC2001(Lithuanian-KBL)
84:PC3001(Estonian-1)	85:PC3002(Estonian-2)
86:PC3011(Latvian-1)	87:PC3012(Latvian-2)
88:PC3021(Bulgarian)	89:PC3041(Maltese)

Barcode Type:

UPC-A	UPC-E
EAN(JAN)13	EAN(JAN)8
CODE39	CODABAR
ITF	CODE93
CODE128	QRcode
PDF417	

DIP-8	Function	ON	OFF
SW-1	Select cutter	No	Yes
SW-2	Select beeper	Yes	No
SW-3	Select print density	Dark	Light
SW-4	Two-byte character code	No	Yes
SW-5	Character per line	42	48
SW-6	Cutter with cash drawer	Yes	No
SW-7	Select baudrate		
SW-8	Select baudrate		

SW-7	SW-8	Baudrate
ON	ON	38400
OFF	ON	115200
ON	OFF	9600
OFF	OFF	19200

```
!"#$%&'()*+,-./0123456789:;<=>?@ABCDEFGHIJKLMNOP
"#$%&'()*+,-./0123456789:;<=>?@ABCDEFGHIJKLMNOPQ
#$%&'()*+,-./0123456789:;<=>?@ABCDEFGHIJKLMNOPQR
$%&'()*+,-./0123456789:;<=>?@ABCDEFGHIJKLMNOPQRS
%&'()*+,-./0123456789:;<=>?@ABCDEFGHIJKLMNOPQRST

!"#$%&'()*+,-./0123456789:;<=>?@ABCDEFGHIJKLMNOPQRSTUVWXYZ[\]^_`
"#$%&'()*+,-./0123456789:;<=>?@ABCDEFGHIJKLMNOPQRSTUVWXYZ[\]^_`a
#$%&'()*+,-./0123456789:;<=>?@ABCDEFGHIJKLMNOPQRSTUVWXYZ[\]^_`ab
$%&'()*+,-./0123456789:;<=>?@ABCDEFGHIJKLMNOPQRSTUVWXYZ[\]^_`abc
%&'()*+,-./0123456789:;<=>?@ABCDEFGHIJKLMNOPQRSTUVWXYZ[\]^_`abcd

ÇüéâäàåçêëèïîìÄÅÉæÆôöòûùÿÖÜø£Ø×ƒáíóúñÑªº¿®¬½¼¡«»
üéâäàåçêëèïîìÄÅÉæÆôöòûùÿÖÜø£Ø×ƒáíóúñÑªº¿®¬½¼¡«»
éâäàåçêëèïîìÄÅÉæÆôöòûùÿÖÜø£Ø×ƒáíóúñÑªº¿®¬½¼¡«»
âäàåçêëèïîìÄÅÉæÆôöòûùÿÖÜø£Ø×ƒáíóúñÑªº¿®¬½¼¡«»
äàåçêëèïîìÄÅÉæÆôöòûùÿÖÜø£Ø×ƒáíóúñÑªº¿®¬½¼¡«»|
```

***** Completed *****